Gulp Tasks

Install

- Gulp Tasks


Required

- Install gulp-cli globally

```
npm install -g gulp-cli
```

Example

- When you complete the above steps, you will see the following screen.


File Edit Selection View Go Run Ter
EXPLORER
OPEN EDITORS
QW.Q.SYSTEM
env
gulpTasks
task
JS jccpa.js 4
JS mongoose.js 2
JS pm2.js 2
JS timesheetApp.js 3
JS wpOpqApp.js 1
OUTLINE
TIMELINE
NPM SCRIPTS
GULP TASKS
jccpaFrontend
jccpaProd
jccpaDev
jccpaVue
exportHotlineCallLog
mongooseBackup
pm2Delete
pm2Restart

- Select the task and click the green start button to start the task.
- You will see the output of the task in Terminal's OUTPUT.
- You can selset the task and click the stop button to stop the task.
- Normal tasks will be automatically disconnected after running. But when doing webpack dev server, the task will be finished first, but the OUTPUT will always be connected.
- In MacOS, click the stop button will disconnect OUTPUT.
- But in Windows will not disconnect OUTPUT. In other words, the app is still running in the background.
    - At this moment, you'd better use the command line to run the gulp task.
    - If you use Gulp Tasks to run the webpack dev server related tasks, you can use some Windows commands to kill the process

```
// open a CMD window


// find the app port, like "8080", the result will show the app's pid
netstat -ano |findstr "port"

// kill the process according to the pid
taskkill /f /t /im "pid"
```

Problem

If you install gulp locally□but encounter the following problems, please try

```
//project dependent download
npm install gulp --no-fund
```



From:
https://wiki.questwork.com/ - **Questwork's Wiki**

Permanent link:
https://wiki.questwork.com/doku.php?id=development:tools:vscode:gulp_tasks:start

Last update: **2022/03/08 02:11**