Android Developer Interview

Basic

- Suppose you have a v-shape array, e.g [1, 12, 31, 44, 51, 54, 23, 22, 10]. How to find the maximum value in a v-shape array?
- 假如我们有一个v-shape数组，如[1, 12, 31, 44, 51, 54, 23, 22, 10]。怎样找出它的最大值？

Android

Question 1

- Describe three common use cases for using an Intent.
- 请说出 Intent 三个常用案例。

Question 2

- Under what condition could the code sample below crash your application? How would you modify the code to avoid this potential problem? Explain your answer.
- 在什麽情况下以下代码会崩溃？你可以怎样避免？请解释。

```
Intent sendIntent = new Intent();
sendIntent.setAction(Intent.ACTION_SEND);
sendIntent.putExtra(Intent.EXTRA_TEXT, textMessage);
sendIntent.setType(HTTP.PLAIN_TEXT_TYPE); // "text/plain" MIME type
startActivity(sendIntent);
```

Question 3

- What is the relationship between the life cycle of an AsyncTask and an Activity? What problems can this result in? How can these problems be avoided?
- AsyncTask 和 Activity 的生命周期有什麽関系？这个関系有可能导致什麽问题？你可以如何避免？

Question 4

- What is difference between Serializable and Parcelable ? Which is best approach in Android ?
- Serializable 和 Parcelable 有什麽分别？那一个在安卓使用比较好？

Question 5

- 我们有以下代码

```
public class MainActivity extends Activity implements OnClickListener {
  final String TAG = "States";
  Button btnActTwo;

  @Override
  public void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.main);
    btnActTwo = (Button) findViewById(R.id.btnActTwo);
    btnActTwo.setOnClickListener(this);
    Log.d(TAG, "MainActivity: onCreate()");
  }

  @Override
  protected void onRestart() {
    super.onRestart();
    Log.d(TAG, "MainActivity: onRestart()");
  }

  @Override
  protected void onStart() {
    super.onStart();
    Log.d(TAG, "MainActivity: onStart()");
  }

  @Override
  protected void onResume() {
    super.onResume();
    Log.d(TAG, "MainActivity: onResume()");
  }

  @Override
  protected void onPause() {
    super.onPause();
    Log.d(TAG, "MainActivity: onPause()");
  }

  @Override
  protected void onStop() {
    super.onStop();
    Log.d(TAG, "MainActivity: onStop()");
  }

  @Override
  protected void onDestroy() {
    super.onDestroy();
    Log.d(TAG, "MainActivity: onDestroy()");
  }
```

```
  @Override
  public void onClick(View v) {
    Intent intent = new Intent(this, ActivityTwo.class);
    startActivity(intent);
  }
}
```

```
public class ActivityTwo extends Activity {
  final String TAG = "States";

  @Override
  public void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.two);
    Log.d(TAG, "ActivityTwo: onCreate()");
  }

  @Override
  protected void onRestart() {
    super.onRestart();
    Log.d(TAG, "ActivityTwo: onRestart()");
  }

  @Override
  protected void onStart() {
    super.onStart();
    Log.d(TAG, "ActivityTwo: onStart()");
  }

  @Override
  protected void onResume() {
    super.onResume();
    Log.d(TAG, "ActivityTwo: onResume()");
  }

  @Override
  protected void onPause() {
    super.onPause();
    Log.d(TAG, "ActivityTwo: onPause()");
  }

  @Override
  protected void onStop() {
    super.onStop();
    Log.d(TAG, "ActivityTwo: onStop()");
  }

  @Override
  protected void onDestroy() {
    super.onDestroy();
    Log.d(TAG, "ActivityTwo: onDestroy()");
```

```
  }
}
```

```
public class ActivityThree extends Activity {
  final String TAG = "States";

  @Override
  public void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.three);
    Log.d(TAG, "ActivityThree: onCreate()");
    this.finish();
  }

  @Override
  protected void onRestart() {
    super.onRestart();
    Log.d(TAG, "ActivityThree: onRestart()");
  }

  @Override
  protected void onStart() {
    super.onStart();
    Log.d(TAG, "ActivityThree: onStart()");
  }

  @Override
  protected void onResume() {
    super.onResume();
    Log.d(TAG, "ActivityThree: onResume()");
  }

  @Override
  protected void onPause() {
    super.onPause();
    Log.d(TAG, "ActivityThree: onPause()");
  }

  @Override
  protected void onStop() {
    super.onStop();
    Log.d(TAG, "ActivityThree: onStop()");
  }

  @Override
  protected void onDestroy() {
    super.onDestroy();
    Log.d(TAG, "ActivityThree: onDestroy()");
  }
```

```
}
```

- Write down the log results at 4 different cases
  - Start MainActivity
  - Invoke onClick() at MainActivity
  - User press back button from ActivityTwo
  - Start ActivityThree

From:
https://wiki.questwork.com/ - **Questwork's Wiki**

Permanent link:
https://wiki.questwork.com/doku.php?id=interview:developer:android:start&rev=1502369150

Last update: **2017/08/10 12:45**