

# iOS Developer Interview

## Question 1

- Consider the following code. What's the value of the **len** variable, and why?
- 参考以下的代码，len的值为何？请解释。

```
var array1 = [1, 2, 3, 4, 5]
var array2 = array1
array2.append(6)
var len = array1.count
```

## Question 2

- Consider the following code. Where is the error and why? How can it be fixed?
- 参考以下的代码，那里出错了？请解释。如何修复？

```
let op1: Int = 1
let op2: UInt = 2
let op3: Double = 3.34
var result = op1 + op2 + op3
```

## Question 3

- Consider the following code. What is the bug and how does it affect memory? How can it be fixed?
- 参考以下的代码，那里出错了以及如何影响内存？如何修复？

```
class Master {
    lazy var detail: Detail = Detail(master: self)
    init() {
        println("Master init")
    }
    deinit {
        println("Master deinit")
    }
}

class Detail {
    var master: Master
    init(master: Master) {
        println("Detail init")
        self.master = master
    }
    deinit {
```

```
        println("Detail deinit")
    }
}

func createMaster() {
    var master: Master = Master()
    var detail = master.detail
}

createMaster()
```

## Question 4

- Consider the following **UITableViewCell** constructor. What is the purpose of the **reuseIdentifier**? What is the advantage of setting it to a non-nil value?
- 参考以下**UITableViewCell**构造数，**reuseIdentifier**的作用是什麼？把它设定为non-nil值有什麼好处？

```
init(style: UITableViewCellStyle, reuseIdentifier: String?)
```

## Question 5

- Write down the log results at 3 different cases
  - Start **MainViewController**
  - Push to **ViewControllerTwo** form **MainViewController**
  - User press back button from **ViewControllerTwo**
- 我们有以下兩段代码，请分别写下以下三种执行后log的结果
  - 开始 **MainViewController**
  - Push to **ViewControllerTwo** form **MainViewController**
  - 用户在 **ViewControllerTwo** 按back button

```
class MainViewController: UIViewController {

    override func viewDidLoad() {
        super.viewDidLoad()
        print("MainViewController :", "viewDidLoad")
    }
    override func viewWillAppearSubviews() {
        super.viewWillAppearSubviews()
        print("MainViewController :", "viewWillAppearSubviews")
    }
    override func viewDidLayoutSubviews() {
        super.viewDidLayoutSubviews()
        print("MainViewController :", "viewDidLayoutSubviews")
    }
    override func viewWillAppear(_ animated: Bool) {
        super.viewWillAppear(animated)
    }
}
```

```
        print("MainViewController :", "viewWillAppear")
    }
    override func viewDidLoad(animated: Bool) {
        super.viewDidLoad(animated)
        print("MainViewController :", "viewDidLoad")
    }

    override func viewWillAppear(animated: Bool) {
        super.viewWillAppear(animated)
        print("MainViewController :", "viewWillAppear")
    }

    override func viewDidDisappear(animated: Bool) {
        super.viewDidDisappear(animated)
        print("MainViewController :", "viewDidDisappear")
    }

    deinit {
        print("MainViewController :", "deinit")
    }
}
```

```
class ViewControllerTwo: UIViewController {
    override func viewDidLoad() {
        super.viewDidLoad()
        print("ViewControllerTwo :", "viewDidLoad")
    }
    override func viewWillLayoutSubviews() {
        super.viewWillLayoutSubviews()
        print("ViewControllerTwo :", "viewWillLayoutSubviews")
    }
    override func viewDidLayoutSubviews() {
        super.viewDidLayoutSubviews()
        print("ViewControllerTwo :", "viewDidLayoutSubviews")
    }
    override func viewWillAppear(animated: Bool) {
        super.viewWillAppear(animated)
        print("ViewControllerTwo :", "viewWillAppear")
    }
    override func viewDidLoad(animated: Bool) {
        super.viewDidLoad(animated)
        print("ViewControllerTwo :", "viewDidLoad")
    }
    override func viewWillDisappear(animated: Bool) {
        super.viewWillDisappear(animated)
        print("ViewControllerTwo :", "viewWillDisappear")
    }
    override func viewDidDisappear(animated: Bool) {
        super.viewDidDisappear(animated)
        print("ViewControllerTwo :", "viewDidDisappear")
    }
    deinit {
        print("ViewControllerTwo :", "deinit")
    }
}
```

Last update:

2017/08/11 interview:developer:ios:start <https://wiki.questwork.com/dokuwiki/doku.php?id=interview:developer:ios:start&rev=1502380939>  
00:02

---

```
}  
}
```

From:

<https://wiki.questwork.com/dokuwiki/> - **Questwork's Wiki**

Permanent link:

<https://wiki.questwork.com/dokuwiki/doku.php?id=interview:developer:ios:start&rev=1502380939>

Last update: **2017/08/11 00:02**

